



Proteector

PANTHERA HP METALLIZED

Panthera, emerging from leading PET lamination factories, offers unmatched stability and a substantial warranty. Its installer-friendly design ensures effortless application and uniform results. Enhanced with superior scratch resistance, it stands as the ideal solution for durable, easy installation and enduring window protection. Even with tinted windows, Panthera is a must: Elevate your existing tint with superior sun heat rejection for unmatched performance.

Width available in: 51, 76, 101, 152 cm



Panthera 295C → **3 PLY & *55µ / Panthera 298C → **4 PLY & *65µ

	Glare Reduction		Total Solar Energy Rejected		Visible Light Transmission	
CLEAR WINDOW 3MM	<div><div></div></div>	9%	<div><div></div></div>	12%	<div><div></div></div>	90%
TINTED WINDOW 3MM	<div><div></div></div>	78%	<div><div></div></div>	34%	<div><div></div></div>	24%
PANTHERA 230C	<div><div></div></div>	29%	<div><div></div></div>	32%	<div><div></div></div>	70%
PANTHERA 255C	<div><div></div></div>	50%	<div><div></div></div>	39%	<div><div></div></div>	54%
PANTHERA 265C	<div><div></div></div>	65%	<div><div></div></div>	47%	<div><div></div></div>	36%
PANTHERA 275C	<div><div></div></div>	75%	<div><div></div></div>	54%	<div><div></div></div>	25%
PANTHERA 285C	<div><div></div></div>	85%	<div><div></div></div>	57%	<div><div></div></div>	16%
PANTHERA 295C	<div><div></div></div>	94%	<div><div></div></div>	59%	<div><div></div></div>	5%
PANTHERA 298C	<div><div></div></div>	97%	<div><div></div></div>	69%	<div><div></div></div>	3%

CONSTRUCTION

- 1 Common scratch-resistant hard layer, allowing good durability and ease of maintenance when cleaning windows.
- 2 High-quality optical polyester, tinted in mass without optical distortion.
- 3 Bonding adhesive.
- 4 High-quality optical polyester, tinted in mass with anti-heat nano-ceramic particles.
- 5 PS adhesive, polymerizing with the glass within 15 days.
- 6 Adhesive protective liner, disposable after installation.

