



The Boreal decorative film allows you to effectively personalise your windows and glass partitions. Decorated with a graduated white mottled effect pattern, arranged in 40 mm linear bands.

Certifications



Warranty SOLAR SCREEN®

5 years

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection

Solar Energy Absorption

Solar Energy Transmission

Installation Type

Interior

Roll Length

50 meters m

Film Composition

PET

Thickness

40μ

Colour From The Outside

WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane



Tinted Single Pane



Reflective Tinted Single Pane



Clear Double Pane



Tinted Double Pane



Reflective Tinted Double Pane



Gas-Filled Double Pane - Low E



Stadip Ext. Clear Double Pane



Stadip Int. Clear Double Pane



✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Europa decorative film allows you to effectively customize your windows and glass partitions. It features a pattern composed of 44mm frosted bands arranged horizontally and separated by 10 mm clear aspect bands.

Certifications



Warranty SOLAR SCREEN®

5 years

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection

Solar Energy Absorption

Solar Energy Transmission

Installation Type

Interior

Roll Length

30.5 meters m

Film Composition

PET

Thickness

40μ

Colour From The Outside

FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane



Tinted Single Pane



Reflective Tinted Single Pane



Clear Double Pane



Tinted Double Pane



Reflective Tinted Double Pane



Gas-Filled Double Pane - Low E



Stadip Ext. Clear Double Pane



Stadip Int. Clear Double Pane



✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Linea 10 decorative film allows you to effectively personalise your windows and glass partitions. It features a pattern composed of white 10 mm bands arranged horizontally and separated by 4 mm clear aspect bands.

Certifications



Warranty SOLAR SCREEN®
5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection
Solar Energy Absorption
Solar Energy Transmission

Installation Type Interior

Roll Length 30.5 meters m

Film Composition PET

Thickness 40μ

Colour From The Outside WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Linea 18 decorative film allows you to effectively personalise your windows and glass partitions. It features a pattern composed of white 18mm bands arranged horizontally and separated by 6mm clear aspect bands.

Certifications


Warranty SOLAR SCREEN®

5 years

See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating

M1


Storage From -5°C To +40°C

3 years


Reach Rohs Compliant

Respected


Widths Available

152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection

Solar Energy Absorption

Solar Energy Transmission

Installation Type

Interior

Roll Length

50 meters m

Film Composition

PET

Thickness

40μ

Colour From The Outside

WHITE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane



Tinted Single Pane



Reflective Tinted Single Pane



Clear Double Pane



Tinted Double Pane



Reflective Tinted Double Pane



Gas-Filled Double Pane - Low E



Stadip Ext. Clear Double Pane



Stadip Int. Clear Double Pane



✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Lineal decorative film, featuring a pattern of opaque horizontal bands, allows you to effectively customize your windows and glass partitions.

Certifications



Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection
Solar Energy Absorption
Solar Energy Transmission

Installation Type Interior

Roll Length 30.5 meters m

Film Composition PET

Thickness 40μ

Colour From The Outside FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The self-adhesive Riga film is decorated with irregular shaped frosted designs, giving a contemporary touch to your windows and glass partitions.

Certifications



Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Visible Light Transmission	0%
Reflection Of External Visible Light	0%
Reflection Of Internal Visible Light	0%
Solar Ratio :	
Solar Energy Reflection	0%
Solar Energy Absorption	0%
Solar Energy Transmission	0%
Reduction In Solar Glare	0%
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	40μ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Sirius decorative film allows you to effectively customize your windows and glass partitions. It features a pattern composed of 18 mm frosted bands arranged horizontally and separated by 6 mm clear aspect bands.

Certifications



Warranty SOLAR SCREEN®

5 years

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Visible Light Transmission	0%
Reflection Of External Visible Light	0%
Reflection Of Internal Visible Light	0%
Solar Ratio :	
Solar Energy Reflection	0%
Solar Energy Absorption	0%
Solar Energy Transmission	0%
Reduction In Solar Glare	0%
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	40μ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Strada decorative film, featuring a pattern of opaque horizontal bands, allows you to effectively customize your windows and glass partitions.

Certifications



Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating M1



Storage From -5°C To +40°C 3 years



Reach Rohs Compliant Respected



Widths Available 152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection
Solar Energy Absorption
Solar Energy Transmission

Installation Type Interior

Roll Length 30.5 meters m

Film Composition PET

Thickness 40μ

Colour From The Outside FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Stratos decorative film allows you to effectively customize your windows and glass partitions. It features a pattern composed of 35 mm frosted bands arranged horizontally and separated by 10 mm clear aspect bands.

Certifications



Warranty SOLAR SCREEN®
5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection
Solar Energy Absorption
Solar Energy Transmission

Installation Type Interior

Roll Length 30.5 meters m

Film Composition PET

Thickness 40μ

Colour From The Outside FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



The Structur decorative film allows you to effectively customize your windows and glass partitions. It is decorated with frosted bands of alternating width (35 mm and 5 mm), separated from each other by 5 mm clear aspect bands.

Certifications



Warranty SOLAR SCREEN®
5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Solar Ratio :

Solar Energy Reflection
Solar Energy Absorption
Solar Energy Transmission

Installation Type Interior

Roll Length 50 meters m

Film Composition PET

Thickness 40μ

Colour From The Outside FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.