



Applied to clear glass, the Mat Blue film bestows a mat blue tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications



Warranty SOLAR SCREEN®
 5 years
 See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
 M1



Storage From -5°C To +40°C
 3 years



Reach Rohs Compliant
 Respected



Widths Available
 152cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	40%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	11%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	43%
Solar Energy Transmission	48%
Reduction In Solar Glare	55%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60µ
Colour From The Outside	BLUE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



Mat Bronze privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through creating subtle ambient lighting conditions.

Certifications


Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating

M1


Storage From -5°C To +40°C

3 years


Reach Rohs Compliant

Respected


Widths Available

152cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	36%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	11%
Total Solar Energy Rejected	39%
Total Solar Energy Rejected 2*	36%
Solar Ratio :	
Solar Energy Reflection	13%
Solar Energy Absorption	37%
Solar Energy Transmission	50%
Reduction In Solar Glare	59%
G-Value	0.71
U-Value	5.62
Shading Coefficient	0.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60μ
Colour From The Outside	BRONZE

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	✗
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	✗
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



Applied to clear glass, the Mat Green film bestows a mat green tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications


Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating

M1


Storage From -5°C To +40°C

3 years


Reach Rohs Compliant

Respected


Widths Available

152cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	45%
Reflection Of External Visible Light	8%
Reflection Of Internal Visible Light	8%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	43%
Solar Energy Transmission	48%
Reduction In Solar Glare	58%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60µ
Colour From The Outside	GREEN

Installation Advice


Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



Mat Grey privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film filters out most natural light creating subtle ambient lighting conditions.

Certifications



Warranty SOLAR SCREEN®
 5 years
 See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
 M1



Storage From -5°C To +40°C
 3 years



Reach Rohs Compliant
 Respected



Widths Available
 152cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	30%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	11%
Total Solar Energy Rejected	39%
Total Solar Energy Rejected 2*	35%
Solar Ratio :	
Solar Energy Reflection	13%
Solar Energy Absorption	39%
Solar Energy Transmission	48%
Reduction In Solar Glare	59%
G-Value	0.71
U-Value	5.63
Shading Coefficient	0.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60μ
Colour From The Outside	GREY

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	✗
Reflective Tinted Double Pane	✗
Gas-Filled Double Pane - Low E	✗
Stadip Ext. Clear Double Pane	✗
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



Applied to clear glass, the Mat Pink film bestows a mat pink tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications



Warranty SOLAR SCREEN®
 5 years
 See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
 M1



Storage From -5°C To +40°C
 3 years



Reach RoHS Compliant
 Respected



Widths Available
 152cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	45%
Reflection Of External Visible Light	11%
Reflection Of Internal Visible Light	11%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	43%
Solar Energy Transmission	48%
Reduction In Solar Glare	55%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60µ
Colour From The Outside	ROSE

Installation Advice


Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



Mat Metal privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film filters out most natural light creating subtle ambient lighting conditions.

Certifications


Warranty SOLAR SCREEN®

10 years
See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating

M1


Storage From -5°C To +40°C

3 years


Reach Rohs Compliant

Respected


Widths Available

152cm

Construction

1. Dyed polyester without optical distortion
2. Bonding adhesive
3. High optical quality polyester, with anti IR metal particles deposit
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	18%
Reflection Of External Visible Light	60%
Reflection Of Internal Visible Light	28%
Total Solar Energy Rejected	80%
Total Solar Energy Rejected 2*	75%
Solar Ratio :	
Solar Energy Reflection	56%
Solar Energy Absorption	33%
Solar Energy Transmission	11%
Reduction In Solar Glare	82%
G-Value	0.2
U-Value	5.08
Shading Coefficient	0.2
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60μ
Colour From The Outside	SILVER

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	✗
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✗
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.



Applied to clear glass, the transparent Mat Yellow film bestows a mat yellow tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications



Warranty SOLAR SCREEN®

5 years

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	45%
Reflection Of External Visible Light	8%
Reflection Of Internal Visible Light	8%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	43%
Solar Energy Transmission	48%
Reduction In Solar Glare	56%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60µ
Colour From The Outside	YELLOW

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.