



The Vogue decorative film is composed of a systematic repeating pattern that customises your windows and glass surfaces. The use of geometric shapes on your glazing or glass partitions is an excellent way to brighten up any space. In this case, the design imitates fluted glass.

Certifications



Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating



Storage From -5°C To +40°C

3 years



Reach Rohs Compliant

Respected



Widths Available

152cm

Construction

1. High optical quality polyester with engraved pattern
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. Film On 600-F0355), do not clean for at least 1 month and do not apply stickers or other adhesives to the film.

Technical Datasheet

Ultraviolet Transmission	15%
Visible Light Transmission	65%
Reflection Of External Visible Light	NC
Reflection Of Internal Visible Light	NC
Total Solar Energy Rejected	NC
Total Solar Energy Rejected 2*	NC
Solar Ratio :	
Solar Energy Reflection	NC
Solar Energy Absorption	NC
Solar Energy Transmission	NC
Reduction In Solar Glare	NC
G-Value	NC
U-Value	NC
Heat Loss Reduction (Winter)	NC
Rejected Infrared (760-2500 Nm)	NC
Shading Coefficient	NC
Installation Type	Indoor
Roll Length	30.5 meters m
Film Composition	PET
Thickness	90µ
Colour From The Outside	DEPOLI

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Advice based on glass surface up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.

The decorative film Vogue 6 consists of a systematic repetitive pattern that personalizes your windows and glass surfaces. Using geometric shapes on your glass or glass partitions is an excellent way to liven up any space.

Certifications



Warranty SOLAR SCREEN®

5 ans

See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating

M1



Storage From -5°C To +40°C

3 ans



Reach Rohs Compliant

Respected



Widths Available

76cm 152cm

Construction

1. Dyed polyester without optical distortion
2. Bonding adhesive
3. High optical quality polyester, with anti IR metal particles deposit
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soap-based water solution (ref. Film On 600-F0355), do not clean before at least 1 month, and do not apply stickers or other adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	15%
Visible Light Transmission	85%
Reflection Of External Visible Light	0%
Reflection Of Internal Visible Light	0%
Total Solar Energy Rejected	0%
Total Solar Energy Rejected 2*	0%
Solar Ratio :	
Solar Energy Reflection	0%
Solar Energy Absorption	0%
Solar Energy Transmission	0%
Reduction In Solar Glare	0%
G-Value	0
U-Value	0
Heat Loss Reduction (Winter)	0
Rejected Infrared (760-2500 Nm)	0
Shading Coefficient	
Installation Type	Interior
Roll Length	30.5m m
Film Composition	PET
Thickness	89μ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Advice based on glass surface area up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.

First full Frosted film, combining discretion and style, shown here in a fluted glass effect, 6mm wide.

Certifications



Warranty SOLAR SCREEN®

5 ans
 See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating M1



Storage From -5°C To +40°C 3 ans



Reach Rohs Compliant Respected



Widths Available 76cm 152cm

Construction

1. Dyed polyester without optical distortion
2. Bonding adhesive
3. High optical quality polyester, with anti IR metal particles deposit
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

Maintenance Instructions

Soap-based water solution (ref. Film On 600-F0355), do not clean before at least 1 month, and do not apply stickers or other adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	15%
Visible Light Transmission	55%
Reflection Of External Visible Light	0%
Reflection Of Internal Visible Light	0%
Total Solar Energy Rejected	0%
Total Solar Energy Rejected 2*	0%
Solar Ratio :	
Solar Energy Reflection	0%
Solar Energy Absorption	0%
Solar Energy Transmission	0%
Reduction In Solar Glare	0%
G-Value	0
U-Value	0
Heat Loss Reduction (Winter)	0
Rejected Infrared (760-2500 Nm)	0
Shading Coefficient	
Installation Type	Interior
Roll Length	30.5m m
Film Composition	PET
Thickness	105μ
Colour From The Outside	FROSTED

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	✓
Reflective Tinted Single Pane	✓
Clear Double Pane	✓
Tinted Double Pane	✓
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	✓
Stadip Ext. Clear Double Pane	✓
Stadip Int. Clear Double Pane	✓

✓ Yes ✗ Not Recommended ! Caution

*Advice based on glass surface area up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.