Design Decorative abstract film



Silver 99 C films are highly effective at reducing solar heat gain, whilst at the same time continuing to allow most natural light to pass through. Solar glare is greatly diminished and its one-way mirror aspect guarantees privacy from prying eyes, whilst affording a modern feel to the exterior of a building.

### Certifications



### Warranty SOLAR SCREEN®

12 years See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating M1



Storage From -5°C To +40°C 3 years



Reach Rohs Compliant Respected



Widths Available 76cm 152cm

# Construction

- Dyed polyester without optical distortion
- 2. Bonding adhesive
- 3. High optical quality polyester, with anti IR metal particles deposit
- 4. PS adhesive, glass polymerization within 15 days
- 5. Protection release liner, disposable after installation

#### **Maintenance Instructions**

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

## **Technical Datasheet**

Ultraviolet Transmission	<1%
Visible Light Transmission	0.5%
Reflection Of External Visible Light	82%
Reflection Of Internal Visible Light	82%
Total Solar Energy Rejected	91%
Total Solar Energy Rejected 2*	88%
Solar Ratio : Solar Energy Reflection	78%
Solar Energy Absorption	18%
Solar Energy Transmission	4%
Reduction In Solar Glare	99%
G-Value	0.09
U-Value	5.1
Shading Coefficient	0.1
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60μ
Colour From The Outside	SILVER

## **Installation Advice**

Vertical position and standard glass surface\*

Clear Single Pane	~
Tinted Single Pane	Ţ
Reflective Tinted Single Pane	<b>✓</b>
Clear Double Pane	ļ
Tinted Double Pane	×
Reflective Tinted Double Pane	<b>✓</b>
Gas-Filled Double Pane - Low E	×
Stadip Ext. Clear Double Pane	×
Stadip Int. Clear Double Pane	×

✓ Yes 

X Not Recommended | Caution

\\*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.