# Metamark MDT

**Translucent Vinyl for Backlit Displays** 



# **Product Description**

Metamark MDT is a premium grade translucent polymeric calendered self-adhesive vinyl for printers using solvent inks. The product has been developed to provide outstanding print performance for backlit applications. The product has a satin finish and is supplied with a solventbased adhesive. MDT is suitable for application onto backlit signs and lightboxes, for interior or exterior use. The satin finish translucent film produces minimal glare and consistent colour transmission.

# **Material Handling**

- Ensure that the material has reached room temperature and a relative humidity of 50% before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

# **Printing Guidelines**

- Suitable for use on Solvent, Eco Solvent, Latex and UV inkjet printers. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- To achieve the correct colour intensity for backlit applications, a double print pass is recommended.

#### **Overlaminating and Application**

- Allow the inks to cure before cutting flush to the print. before use, or overlaminating, this is usually 24-48 hours
- The matched laminate for MDT is MetaGuard 703. For all other laminates the user should determine suitability.
- The user should determine suitability of substrate, refer to the web site. Not recommended for use on low energy surfaces.
- Refer to www.metamark.co.uk for application guidelines.

Face Film		Finishes			
Face Film Gauge Tensile Strength	Polymeric calendered PVC 80 micron nominal 58N/25mm MD / 54N/25mm TD	Finishes Available Light Transmission	MDT-600 38%	Satin white	
·	nominal	<b>Roll presentation</b>			
Elongation at break	180% MD nominal		700 50	441	
Adhesive		Roll sizes and net weights	760mm x 50m 11kg 1370mm x 50m 18kg		
			1520mm x 50m	22kg	
Type Weight	Crystal clear solvent-based acrylic 22gsm nominal	Presentation	Face film outwards.		
Adhesion to glass 20 mins	15N/25mm nominal	Durability			
Adhesion to glass 24 hour	20N/25mm nominal				
Perceived tack	Medium	Shelf Life	2 years		
Application temperature	+5°C to +60°C	External weathering	5 years. This refers to the unprinted		
Service temperature	-30°C to +110°C		vinyl. Refer to ink ma durability of the finish		
Release Liner		Fire Rating	Class B. BS EN 13501-1:2007		
		Chemical Resistance	The unprinted film is	resistant to	
Print	'Metamark T series' blue print		mineral oils, fats and	<i>'</i>	
Weight	140 gsm nominal		solvents, mild acids,		
Туре	Layflat kraft with PE coating		e.g. diesel oil, gasolin	· •	
			hydraulic oil, antifreez	ze, soap suus, elc.	

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark DigitalVinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. Please Note: The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

#### Metamark (UK) Limited

⊃ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147 Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540 sales@metamark.co.uk www.metamark.co.uk